



HOUSING

Poles: 3
 Material: Nylon 66, UL94V-0
 Q'ty: 500, 1000 pcs/bag

ELECTRICAL:

CURRENT RATING: 7.0A AC DC.
 VOTAGE RATING: 250V AC DC.
 TEMPERATURE RANGE: -25°C~+85°C.
 CONTACT RESISTANCE: 20m Ohm Max.
 INSULATION RESISTANCE: 1000 M Ohm Min.
 WITHSTANDING VOTAGE: 1500V AC/MINUTE.
 APPLICABLE WIRE: AWG #22 TO #18

VH70-H-03-LF
 LEADFREE

RoHS Compliant

All Connectors

www.allconnectors.de
 Tel.: 0015 711 7009503
 70734 Filderstadt, Germany

info@allconnectors.de
 Fax: 0015 711 7009504
 K: 11.06.2011, 25

PART NO. VH70-H-03

DWG NO. VH70-H-03

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2
 .XX ±
 .XXX ±
 AWG

DESCRIPTION: **PITCH 7.0 HOUSING**

AREA REVISIONS HK DATE

AREA REVISIONS HK DATE