



Technical Remarks:

- 1, The part must be free of hazard burrs, pointed, sharp edges and mechanical damage.
- 2, The Plating should be uniform, bright, nodefects such as fog spot and delamination.
- 3, Tolerance is not injected by GB1804-M-class.

| | | |
|--------------------|--|--------------|
| Symbol Description | | Control size |
|--------------------|--|--------------|

| | | | | | | | |
|----------|-------------|------------|------|---|-------------------|-------|---|
| | | | | Plating | Cu/Ep. Cu10Sn3-5m | | |
| | | | | UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MM | | | <small>www.allconnectors.com Tel: 0049 7141 7099008 20744 Filderstadt - Germany</small> |
| | | | | TOLERANCES: | | | |
| MARK | REV | NAME | DATE | WHOLE NO. | DECIMAL | ANGLE | MATERIAL :BRASS (H62 Y δ=0.6) |
| | | | | ±0.2 | ±0.1 | ±0.5° | |
| DESIGNER | XUWUYU | 2008.07.18 | SIZE | REV | SCALE | PAGE | MODEL: OH-538506 |
| CHECKED | MEIJIAOLONG | 2008.07.18 | A4 | | 5:1 | 1/1 | FILE NO.: ZR7.731.262 |
| APPROVAL | JIYAOHU | 2008.07.18 | | | | | |