



MATERIAL :
 INSULATOR : PBT+30% GLASS FIBER (UL94V-0)
 CONTACT : PHOSPHOR BRONZE OR BRASS
 CONTACT PLATED : GOLD OR TIN OVER NICKEL

SPECIFICATION :
 CURRENT RATING : 1AMP.
 WITHSTANDING VOLTAGE : AC 500V R.M.S
 INSULATION RESISTANCE : 1000MEGOHMS MINIMUM
 AT DC 500V.
 CONTACT RESISTANCE : 15 MILLIOHMS MAXIMUM.
 OPERATING TEMPERATURE ; -40°C~105°C.

HPCP-PDPZ-xxx-LF
 LEADFREE
 RoHS Compliant

PIN	A	B	C	D
20	24.15	19.73	11.43	12.43
40	36.85	32.43	24.13	34.13
50	43.2	38.78	30.48	40.48
68	54.63	50.21	41.91	51.91
80	62.25	57.83	49.53	59.53

All Connectors
 www.allconnectors.de
 info@allconnectors.de
 TEL: 0049 711 3095008
 FAX: 0049 711 3095004
 20794 Hildesheim - Germany

PART NO. HPCP-PDPZ-xxx		CHECKED BY CY		TOLERANCES ARE		DESCRIPTION:			
DWG NO. HPCP-PDPZ-xxx		DRAWING BY		X ± 0.2 XX ± 0.1 XXX ± 0.05 AWG					
FILE NO.		PROJECTION		UNIT / mm		AREA	REVISIONS	HK	DATE
SCALE 1:1		[Symbol]							