





2.54mm(.100") Wire To Wire And Wire To Board Connector



SPECIFICATIONS:

- Current Rating:3AAC,DC
- Voltage Rating:250V AC,DC
- Operating Temperature:-40℃~+105℃
- Contact Resistance:10mΩ max.
- Insulation Resistance:5000MΩ Min.
- Withstanding Voltage:750V AC/minute
- Material:Nylon66 UL94V-0
- Use With:M2050Series



Ordering Information And Dimensions

Part NO.		Dimensions		Part NO.		Dimensions	
TYP UL94V-0	Circuits	Dim:A	Dim:B	TYP UL94V-0	Circuits	Dim:A	Dim:B
M2052-2-W	2	5.05	2.54	M2052-10-W	10	25.37	22.86
M2052-3-W	3	7.60	5.08	M2052-11-W	11	27.91	25.40
M2052-4-W	4	10.14	7.62	M2052-12-W	12	30.45	27.94
M2052-5-W	5	12.67	10.16	M2052-13-W	13	32.99	30.48
M2052-6-W	6	15.21	12.70	M2052-14-W	14	35.53	33.02
M2052-7-W	7	17.75	15.24	M2052-15-W	15	38.07	35.56
M2052-8-W	8	20.29	17.78	M2052-16-W	16	40.61	38.10
M2052-9-W	9	22.83	20.32	M2052-17-W	17	43.15	38.10



www.allconnectors.de
Tel.: 0049 /11 7009503
70794 Filderstadt - Germany

info@allconnectors.de
Fax: 0049 /11 7009504
Kellenerstr. 25