



▽ DIP3 PITCH 2.54MMX15.24MM I.D.C. DIP PLUG FOR PITCH 1.27MM CENTER FLAT RIBBON CABLE

- MATERIAL & FINISH**
- *INSULATOR: PBT+GLASS FIBER UL 94V-0
 - *CONTACT: BRASS
 - *FINISH: GOLD-PLATED OVER NICKEL
- SPECIFICATIONS**
- *CURRENT RATING: 1A AC,DC
 - *VOLTAGE RATING: 250V AC,DC
 - *TEMPERATURE RANGE: -40°C TO +105°C
 - *CONTACT RESISTANCE: 20MΩ MAX
 - *INSULATION RESISTANCE: 1,000MΩ MIN
 - *WITHSTANDING VOLTAGE: 500V AC/MIN

PART NO	DIM A	DIM B
IP06-C2-10	10.16	17.96
IP06-C2-14	15.24	23.04
IP06-C2-16	17.78	25.58
IP06-C2-18	20.32	28.12
IP06-C2-20	22.86	30.66
IP06-C2-24	27.94	35.74

PART NO	DIM A	DIM B
IP06-C2-26	30.48	38.28
IP06-C2-28	33.02	40.82
IP06-C2-32	38.10	46.00
IP06-C2-34	40.64	48.44
IP06-C2-36	43.18	50.98
IP06-C2-40	48.26	56.06

DIMENSIONS:MM

Allconnectors
 www.allconnectors.de
 TEL: 0049 /11 7092503
 70794 Filderstadt - Germany

info@allconnectors.de
 FAX: 0049 /11 7092504
 Kellenersstr. 25

PART NO. IP06-C2-xx

DWG NO. IP06-C2-xx

CHECKED BY CY

DRAWING BY

TOLERANCES ARE

- .X ± 0.2
- .XX ±
- .XXX ±
- AWG

DESCRIP TION:

IDC DIP PLUG
 PITCH 2.54mm*15.24mm

UNIT / mm

SCALE 1:1

PROJECTION

AREA

REVISIONS

HK

DATE