



HF-C2S-xxx-LF
LEADFREE
RoHS Compliant

100	68.40 [2.693]	65.50 [2.579]	62.23 [2.450]
80	55.70 [2.193]	52.80 [2.079]	49.53 [1.950]
68	48.08 [1.893]	45.18 [1.779]	41.91 [1.650]
60	43.00 [1.693]	40.10 [1.579]	36.83 [1.450]
50	36.65 [1.443]	33.75 [1.329]	30.48 [1.200]
40	30.30 [1.193]	27.40 [1.079]	24.13 [0.950]
34	26.49 [1.043]	23.59 [0.929]	20.32 [0.800]
30	23.95 [0.943]	21.05 [0.829]	17.78 [0.700]
26	21.41 [0.843]	18.51 [0.729]	15.24 [0.600]
24	20.14 [0.793]	17.24 [0.679]	13.97 [0.550]
20	17.60 [0.693]	14.70 [0.579]	11.43 [0.450]
16	15.06 [0.593]	12.16 [0.479]	8.89 [0.350]
14	13.79 [0.543]	10.89 [0.429]	7.62 [0.300]
10	11.25 [0.443]	8.35 [0.329]	5.08 [0.200]
Number of Position	A	B	C
	DIMENSIONS		

MATERIALS

- HOUSING : MATERIAL: NYLON66. (UL 94V-0) BLACK
47: MATERIAL: PBT. (UL 94V-0) BLACK
- TERMINAL : COPPER ALLOY (t=0.30mm).
GOLD FLASH PLATED ON CONTACT AREA
UNDER NICKEL PLATED.

SPECIFICATION

- CURRENT RATING : 1 A MAX.
- DIELECTRIC WITHSTANDING VOLTAGE :
500V AC R.M.S. FOR ONE MINUTE.
- INSULATION RESISTANCE : 500MΩ MIN.
AT 500V DC.
- CONTACT RESISTANCE : 30mΩ MAX.
- OPERATING TEMPERATURE : -40°C TO +85°C.

All Connectors

www.allconnectors.de
Tel: 0049 711 7009503
70754ilderstact - Germany

info@allconnectors.de
Fax: 0049 711 7009504
Kettnerstr. 25

PART NO. HF-C2S-xxx

DWG NO. HF-C2S-xxx

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2
.XX ± 0.1
.XXX ±
AWG

DESCRIPTION:

IDC SOCKET 1.27X2.54mm KIT ROHS

AREA

REVISIONS

HK

DATE