

#### NOTES

##### 1.MATERIAL

- 1.1 Insulator: P.B.T. +15% G.F. UL-94V-0
- 1.2 Contact: Phosphor Bronze
- 1.3 Plating: Gold Or Nickel Plated

##### 2.SPECIFICATION

- 2.1 Current Rating: 3Amp
- 2.2 Dielectric Withstanding: AC 1000V min.Per minute
- 2.3 Insulation Resistance: 1000M ohms At DC 500V
- 2.4 Contact Resistance: 25 M ohms Max
- 2.5 Contact Insertion Force: 1kg max
- 2.6 Contact Separation force: 70g min
- 2.7 Operating Temperature: -55°C To +85°C

**All Connectors**

www.allconnectors.de  
Tel.: 0049 711 7009503  
70794 Filderstadt - Germany

info@allconnectors.de  
Fax: 0049 711 7009504  
Kettnerstr. 25

**RoHS Compliant**

DRAWING BY CY  
CHECKED BY GENIUS  
UNIT/mm SCALE 1:1  
DATE  
SIZE A4


TOLERANCES ARE

X ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PJECTION



**ORDER INFORMATION**



DESCRIPTION: MJ 2A黑 磷銅半面金