



NOTES:

1. MATERIAL: SILICONE ELASTOMER VMQ
2. TEMPERATURE RANGE IN DRY ATMOSPHERE: -60°C+200°C
3. TEMPERATURE RANGE IN WATER STEAM: +140°C
4. ROHS COMPLIANCE
5. PART NO.

Z - F B 2 B * * 4 1 1 * 0

PRODUCT TYPE
F=SNAP LATCH METAL

COLOUR
SEE TABLE 2

PRODUCT MODEL
B=BEND RELIEF

DIM. A
SEE TABLE 1

PRODUCT STYLE
2B=2B STYLE

| DIM.A |
|-------------------------|
| 40=CABLE OD 4.0mm-4.4mm |
| 45=CABLE OD 4.5mm-5.0mm |
| 51=CABLE OD 5.1mm-5.6mm |
| 57=CABLE OD 5.7mm-6.2mm |
| 63=CABLE OD 6.3mm-7.0mm |
| 71=CABLE OD 7.1mm-7.9mm |
| 80=CABLE OD 8.0mm-9.0mm |

TABLE 1

| COLOUR |
|----------|
| B=Blue |
| W=White |
| G=Gray |
| Y=Yellow |
| M=Brown |
| N=Black |
| R=Red |
| S=Orange |
| V=Green |

TABLE 2

| | | | | | |
|---|---------|---|-----------------------|-------------------------|-----|
| UNITS mm INCH | | NAME: SNAP LATCH METAL 2B BEND RELIEF | | All Connectors | |
| GENERAL TOLERANCES: (UNLESS SPECIFIED) | | PART NO: Z-FB2B**411*0 | | TITLE: CUSTOMER DWG. | |
| | mm | INCH | APPD: Seawen 12/12/13 | DWG NO: 010-0000-B75 | |
| 4 PLACE | ± ** | ± **.** | CHKD: Annie 12/12/13 | C | |
| 3 PLACE | ± 0.30 | ± **.** | DRAWN: Alex 12/12/13 | SCALE: SHEET: REV: | |
| 2 PLACE | ± 0.50 | ± **.** | | 2.5/1 | 1/1 |
| 1 PLACE | ± 0.80 | ± **.** | | | X1 |
| ANGULAR: | X° ± 2° | X° ± **.** | | | |

| REV. | DESCRIPTION | DATE | APPD |
|------|-------------|----------|--------|
| X1 | NEW RELEASE | 12/05/13 | Seawen |