



材質 MATERIAL:
 A. 外套管 COVER: PE+2L
 B. 中套管 SHELL: ABS
 C. 銅板 METAL SHIELD: 黃銅鍍銀
 BRASS NICKEL PLATED
 D. 膠芯 HOUSING: NYLON66+GF
 E. 針 CONTACT: 黃銅鍍銀
 BRASS GOLD FLISH PLATED

SPECIFICATIONS:
 1. RATING: 11V AC 1A MAX
 OR 12V DC 2A MAX.
 2. INSULATION RESISTANCE:
 50M OHM MIN AT 500V DC.
 3. DIELECTRIC STRENGTH:
 500V AC / 1 MINUTE.

7.0φ	BACK SHELL
6.0φ	BACK SHELL
⊗	5.0φ BACK SHELL (STANDARD)
	COVER DIM.

TABLE A

MDA-P-07B-LF
 LEADFREE
 RoHS Compliant

Allconnectors

www.allconnectors.de info@allconnectors.de
 Tel: 0049 711 7009504 Fax: 0049 711 7009504
 70794 Filzschull, Germany Kellerestr. 25

PART NO. MDA-P-07B		CHECKED BY CY		TOLERANCES ARE .X±0.2 .XX±0.1 .XXX± AWG	DESCRIP TION:
DWG NO. MDA-P-07B		DRAWING BY			
FILE NO.		PROJECTION		AREA	REVISIONS
UNIT / mm	SCALE 1:1			HK	DATE