



<input type="checkbox"/>	7.0# BACK SHELL
<input type="checkbox"/>	6.0# BACK SHELL
<input checked="" type="checkbox"/>	5.0# BACK SHELL (STANDARD)
<input type="checkbox"/>	COVER DIM.

TABLE A

Materials:

- A.BOOT: PVC
- B.MIDDLE HOOD: ABS
- C.METAL PART: COPPER, NICKEL PLATED
- D.INSULATOR: PC
- E.PIN CONTACT: COPPER,SILVER

SPECIFICATIONS:

- 1.RATION: 100V AC 1A MAX or 12V DC 2A MAX.
2. INSULATION RESISTANCE: 50M OHM MIN at 250V DC.
3. DIELECTRIC STRENGTH: 250 V AC / 1 MINUTE.
4. CONTACT RESISTANCE: 30M OHM MAX.
5. INSERTION FORCE: 4.5KG MAX.
6. WITHDRAWAL FORCE: 0.9KG ~ 3KG.

**Allconnectors**

www.allconnectors.de  
Tel.: 0049 711 7009503  
70394 Hildesheim, Germany

info@allconnectors.de  
Fax: 0049 711 7009504  
Kottoweststr. 25

PART NO. MDA-S-xx		CHECKED BY CY	TOLERANCES ARE X±0.2 XX± XXX± AWG	DESCRIPTION: MINI DIN JACK ASSY	AREA	REVISIONS	HK	DATE
DWG NO. MDA-S-xx								
FILE NO.		PROJECTION						
UNIT / mm	SCALE 1:1							