



P.C.B. LAYOUT

MATERIAL
 INSULATOR: LCP OR PBT UL94V-0
 CONTACT: Brass, Gold/Tin plated
 SHELL: Brass/Spcc, Tin plated or Nickel plated
 ENVIRONMENTAL
 OPERATING TEMPERATURE: -55°C~105°C
 ELECTRICAL
 CONTACT CURRENT RATING: 1 Amp
 DIELECTRIC WITHSTANDING : AC 1000V/min.R.M.S.
 INSULATION RESISTANCE: 500M Ω min.at 500V DC
 CONTACT RESISTANCE: 30m Ω Max

MDJ-F-07B-LF
 LEADFREE
 RoHS Compliant

All connectors

www.allconnectors.de
 Tel: 0049 711 700503
 70704 Filderstect - Germany

info@allconnectors.de
 Fax: 0049 711 700504
 Kettnerstr. 25

PART NO. MDJ-F-07B

DWG NO. MDJ-F-07B

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

X ± 0.2
 .XX ±
 .XXX ±
 AWG

DESCRIPTION:

迷你單層特殊型TP母半金黑
 (銅殼鍍錫無彈不加彈) RoHS

AREA

REVISIONS

HK

DATE