



P.C.B. LAYOUT

MATERIAL
 INSULATOR: PBT UL94V-0
 CONTACT: Phosphor bronze, Gold/Tin plated
 SHELL: Brass, TIN Plated Or Nickel/Tin Plated
ENVIRONMENTAL
 OPERATING TEMPERATURE: -55°C~105°C
ELECTRICAL
 CONTACT CURRENT RATING: 1 Amp
 DIELECTRIC WITHSTANDING : AC 1000V/min.R.M.S.
 INSULATION RESISTANCE: 500MVmin.at 500V DC
 CONTACT RESISTANCE: 30mV Max

Allconnectors

www.allconnectors.de
 info@allconnectors.de
 Tel.: 0049 711 7065903
 Fax: 0049 711 7065904
 70734 Filderstadt - Germany
 Kettnerstr. 25

PART NO. MDJ-F-08

DWG NO. MDJ-F-08

FILE NO.

UNIT / mm

CHECKED BY CY

DRAWING BY

PROJECTION

SCALE 1:1

TOLERANCES ARE

.X±0.2

.XX±

.XXX±
 AWG

DESCRIPTION:

迷你單層8P母半金黑
 (鐵殼鍍錫無彈不加彈)

AREA	REVISIONS	HK	DATE