



MDJ-F1-06-LE
LEADFREE
RoHS Compliant

Specification:

Contact Resistance: 30m Ohm Max.

Insulation Resistance: 100M Ohm Min.AT 500V DC

Rated Voltage And Current: DC12V.2A Max;AC 100V.1A Max

Dielectric Withstanding Voltage: 250V AC For 1 Minute

Durability (Life Test): 100 Cycles

Insertion Force: 4.0KG Maximum.

Extraction Force: 0.9KG Minimum.

NO.	NAME	MATERIAL	FINISH	Q'TY
1	HOUSING	NYLON PA9T G.F.	BLACK	1
2	CONTACT	PHOS. BRONZE T:0.2	Gold:1~3u"; NI:40~60u"; TIN:120u" (100% pure Tin of lead free plating)	6
3	SHIELD	BRASS T:0.3	TIN PLATED Sn:120~200u"	1
4	BACK COVER	NYLON PA9T G.F.	BLACK	1

All Connectors

www.allconnectors.de
Tel.: 0049 711 7009508
70794 Filderstadt - Germany

info@allconnectors.de
Fax: 0049 711 7009514
Kettnerstr. 25

PART NO. MDJ-F1-06

DWG NO. MDJ-F1-06

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

X ± 0.25

.XX ± 0.13

.XXX ± 0.05

ANG

DESCRIPTION: MINI DIN JACK FLAT 6 PIN DIP

AREA

REVISIONS

HK

DATE