

MATERIALS:

- A. BOOT: PE + 2L
- B. MIDDLE HOOD: PA-757/ PS-475
- C. METAL SHELL:
COPPER NICKEL PLATED
- D. INSULATOR: NYLON 6 + G.F.
- E. PIN CONTACT:
BRASS GOLD FLASH

SPECIFICATIONS:

1. RATION: 100V AC 1A MAX or 12V DC 2A MAX.
2. INSULATION RESISTANCE: 50M OHM MIN at 250V DC.
3. DIELECTRIC STRENGTH: 250 V AC / 1 MINUTE.
4. CONTACT RESISTANCE: 30M OHM MAX.
5. INSERTION FORCE: 4.5KG MAX.
6. WITHDRAWAL FORCE: 0.9KG ~ 3KG.
7. OPERATING TEMPERATURE: -20°C ~ 105°C

	7.0ø BACK SHELL
	6.0ø BACK SHELL
X	5.0ø BACK SHELL (STANDARD)
	COVER DIM.

TABLE A

MDL-J-xx-LF
LEADFREE
RoHS Compliant

All connectors

www.allconnectors.de
Tel.: 0049 711 7009508
70794 Filderstadt - Germany

info@allconnectors.de
Fax: 0049 711 7009504
Kettnerstr. 25

PART NO. MDL-J-xx

DWG NO. MDL-J-xx

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIPTION:

Mini Din Jack
Lock Ass'y Type

AREA

REVISIONS

HK

DATE