

Section: A–A

Signal Name	
Pin Number	USB
S1	VBUS
S2	D–
S3	D+
S4	GDN

Signal Name	
Pin Number	1394
S1	VP
S2	VG
S3	TPB*
S4	TPB
S5	TPA*
S6	TPA

Signal Name	
Pin Number	eSATA
S1	GND
S2	A+
S3	A–
S4	GND
S5	A–
S6	A+
S7	GND





P.C.B Layout t=1.60mm
Top View

Unit:mm

Standard	Dim A
CUIE–M212DGY–72	2.15~2.30
CUIE–M212DGY–71	3.10

NOTES:

1. Material:
   - Housing: PBT+30%G.F, UL 94V-0 Rated.
   - Color: Yellow.
   - Retainer: Nylon66+30%G.F,UL 94V-2 Rated.
   - eSATA Contact: Brass.
   - Plating: Gold Plating over Nickel on Contact Area. Tin Plating on Solder Tail.
   - IEEE 1394 Contact: Brass.
   - Plating: Gold Plating over Nickel on Contact Area. Tin Plating on Solder Tail.
   - USB Contact: Phosphor Bronze.
   - Plating: Gold Plating over Nickel on Contact Area. Tin Plating on Solder Tail.
   - Front Shell:SUS301,Nickel Plating.
   - Back Shell:SUS301.
2. eSATA Electrical Specification:
   - Operation Voltage: 100VAC Max.
   - Current Rating: 1.5 Ampere per Contact.
   - Contact Resistance: 30mΩ Max.
   - Insulation Resistance: 1000MΩ Min.
   - Dielectric Withstanding Voltage: 500 VAC.
3. IEEE 1394 Electrical Specification:
   - Operation Voltage:40 VAC Max.
   - Current Rating: 1.5 Ampere per Contact.
   - Contact Resistance: 30 mΩ Max.
   - Insulation Resistance: 100 MΩ Min.
   - Dielectric Withstanding Voltage: 500V AC.
4. USB Electrical Specification:
   - Rated Voltage and Current: 1.5A at 250V AC Min.
   - Contact Resistance: 30mΩ Max.
   - Insulation Resistance: 1000MΩ Min at 500V DC.
   - Dielectric Withstanding Voltage: 500 V AC for 1Minute.
5. Environmental:
   - Operating Temperature: -55°C to +85°C

Part Number:

CUIE-M212DGY-72

- USB +IEEE 1394+eSATA
- M: Male
- 21: 4+4+6+7P
- 2: Stacked Type
- D: DIP Type
- 1: DIP 3.1mm; 2: DIP 2.15mm
- 7: 2*USB+1*IEEE 1394+1*eSATA
- Y: Yello Color
- G: Gold Flash

REV	DATE	DESCRIPTION
A	04/21/10	RELEASED FOR PRODUCTION

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM
TOLERANCES ARE:
DECIMALS ANGLES
.X ± .38 ± 3°
.XX ± .25
.XXX ± .20

DO NOT SCALE DRAWING

CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE

APPROVALS		DATE
DRAWN	Chris	04/21/10
CHECKED	Cindy	04/21/10
APPV	Jason	04/21/10

SHEET 1 OF 1 | SCALE NONE

All Connectors
www.allconnectors.de
Tel.: 0049 /211 /600503
70794 Filderstadt Germany
Info@allconnectors.de
Fax: 0049 /211 /600504
Kottomerstr. 25

DESCRIPTION: 2*USB+IEEE 1394+eSATA Plug, 4+4+6+7P, Stacked, DIP Type, Yellow Color, Gold Flash

DWG. NO. CUES-M21-F05 | REV. A