



### Specifications

|                        |                      |
|------------------------|----------------------|
| Contact Resistance:    | 30mΩ Max.            |
| Dielectric Strength:   | 250V AC / 1 Minute   |
| Insulation Resistance: | 50MΩ Min. at 250V DC |
| Rating:                | 100V AC 1A Max.      |
|                        | 12V DC 2A Max.       |
| Insertion Force:       | 4.5Kg Max.           |
| Withdrawal Force:      | 0.6Kg~3Kg            |

### Characteristics

|             |
|-------------|
| Solder Type |
| PCB Mount   |
| 13 Pin      |
|             |
|             |
|             |

### Substitute Items



|        |
|--------|
| D-1091 |
| D-1092 |
|        |
|        |
|        |
|        |

### Mating Items

|        |
|--------|
| D-6002 |
| D-6003 |
| D-6005 |
| D-6006 |
| D-6007 |
| D-6008 |
| D-6009 |

### Arrangement of Contacts

13P



SIDE VIEW

**Allconnectors**

www.allconnectors.eu | info@allconnectors.eu  
Tel. +49 (0)711 / 358 110 20 | Fax +49 (0)711 / 358 110 25

Multi-Pole Socket / 13 Pin

D-1090

DATE

UNIT: mm



1 / 1

A0

A4