

NOTE:

1.SAFETY:


- 1-1.RATING: 0.5A/250Vac.
- 1-2.CONTACT RESISTANCE: 30mOhm MAX.
- 1-3.INSULATION RESISTANCE: 100Mohm MIN.
- 1-4.DIELECTRIC WITHSTANDING VOLTAGE: 100Vac/1minute.
- 1-5.DURABILITY: 10,000cycles.

2.MATERIAL:

- 2-1.PIN:PHOSPHOR BRONZE.
- 2-2.HOUSING:LCP UL 94-V0 rated
- 2-3.LATCH:STAINESS #301
- 2-4.SHELL:STAINESS #301

3.PLATING:

- 3-1.PIN:GOLD FLASH MIN ON CONTACT AREA.



BOM	
5	CONTACT
2	SHELL
1	HOUSING
数量	零件

All connectors

www.allconnectors.de info@allconnectors.de
Tel.: 0049 711 7009503 Fax: 0049 711 7009504
70791 Hilderstadt - Germany Kettenerstr. 25

RoHS Compliant

DRAWING BY CY
CHECKED BY GENIUS
UNIT/mm SCALE 1:1
DATE
SIZE A4

TOLERANCES ARE

X ±
.X ±
.XX ±
.XXX ±
ANG ±

PROJECTION



ORDER INFORMATION

MISB-PS-5A-LF
SERIES LEADFREE
5 PIN A TYPE
SOLDER
MALE

DESCRIPTION: MICRO USB 5PATYPE MALE SOLDER