



Note:

1.Material:

- 1.1 Housing: High temperature thermoplastic with g.f,UL94v-0
- 1.2 Contact: copper alloy,t=0.20mm
- 1.3 Shell: copper alloy,t=0.25mm

2.Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.
- 2.3 Contact resistance: 50 mW Max.
- 2.4 Insulation resistance: 100 MW Min.
- 2.5 Total mating force: 3.57 Kgf Max.
- 2.6 Total unmating force: 1.0 Kgf Min.0.81~2.05 Kgf Min.after 10000 insertion/extraction cycles
- 2.7 Temperature range: -30°C~80°C

RoHS Compliant

All Connectors

www.allconnectors.de
 Tel.: 0049 711 7009502
 70794 Filderstadt, Germany

info@allconnectors.de
 Fax: 0049 711 7009504
 Kettenstr. 25

DRAWING BY CY	
CHECKED BY GENIUS	
UNIT / mm	SCALE 1 : 1
DATE	
SIZE A4	PJECTION

TOLERANCES ARE

X ±
 X ± 0.25
 .XX ± 0.20
 .XXX ± 0.10
 ANG ±



ORDER INFORMATION

MISB-SWP40-5B-LF
 SERIES | | | LEADFREE
 | | | 5 PIN B TYPE
 | | | POST 4.0mm
 | | | 90°SMT
 | | | FEMALE

DESCRIPTION: MICRO USB 5P FEMALE B TYPE(SMT SHELL)有柱