

備註 / NOTE :

1. 安規 / SAFETY :

- 1-1. 規格 / RATING : 100V AC MAX or 12V DC 2A MAX
- 1-2. 絕緣阻抗 / INSULATION RESISTANCE : 200MΩ MIN at 250V DC
- 1-3. 絕緣耐壓 / WITHSTANDING : 250V AC at 1 MINUTE
- 1-4. 接觸阻抗 / CONTACT RESISTANCE : 50mΩ MAX AT DC 1A

2. 材質 / MATERIAL :

- 2-1. 膠芯 / HOUSING : NYLON GF33% UL94-V0
- 2-2. 針 / PIN : 磷銅 / PHOSPHOR BRONZE
- 2-3. 上線夾 / PLASTIC UP COVER : PBT 30% GF-94V0

- 2-4. 下線夾 / PLASTIC DOWN COVER : PBT 30% GF-94V0
- 2-5. 外套 / PLASTIC COVER : P.P UL 94-V0
- 2-6. 上蓋 / METAL UP COVER : 不鏽鋼
- 2-7. 下蓋 / METAL DOWN COVER : 不鏽鋼 / STAINLESS
- 2-8. 線夾 / CABLE FIXED : 不鏽鋼 / STAINLESS

3. 電鍍 / PLATING :

- 3-1. 針 / PIN: CONTACT AREA : GOLD 5u"
SOLDER AREAS : TIN-LEAD 100u"MIN

RoHS Compliant

TOLERANCES ARE

All Connectors

DRAWING BY CY

CHECKED BY GENIUS


UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION



ORDER INFORMATION

PCM-PA-32-LF
SERIES | T LEADFREE
32WAY
ASSEMBLY
MALE

www.allconnectors.de
Tel.: 0049 711 7009503
70794 Filderstadt - Germany

info@allconnectors.de
Fax: 0049 711 7009504
Kettnerstr. 25

DESCRIPTION: PCMCIA 32PIN 公座