


Material:
 Plastic Body : LCP+35%GF, Color Black.
 Slider : LCP+35%GF, Color Black.

Contact :Phosphor Bronze Alloy (C5210R-EH)
 Contacts Plating:Contact area: Gold 10 micro inches (Min.)
 Solder area: Gold flash
 All under-plated Ductile Nickel 50 micro inches (Min.)

Shell :SUS304R-3/4H
 Plating:
 Contact area: Gold flash
 Solder area: Gold flash
 All under-plated Ductile Nickel 12 micro inches (Min.)

Spring : Piano Wire
 Drag Link : SUS304



PART NAME	Q'TY	MATERIAL
BODY	1	LCP+35%GF
SLIDER	1	LCP+35%GF
CONTACT	1	C5210R-EH
SHELL	1	SUS304R-3/4H
DRAG LINK	1	SUS304
SPRING	1	PIANO WIRE

PIN NUMBER	PIN ASSIGNMENT	PIN NUMBER	PIN ASSIGNMENT
1	DAT2	6	VSS
2	CD/DAT3	7	DAT0
3	CMD	8	DAT1
4	VDD	Cd	CARD DETECTION
5	CLK	G	GROUND

All Connectors

www.allconnectors.de
 Tel.: 0049 711 7009508
 70754 Filztersbach - Germany

info@allconnectors.de
 Fax: 0049 711 7009504
 Kellnersstr. 25

RoHS Compliant

DRAWING BY CY
 CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1


DATE

SIZE A4

TOLERANCES ARE

X ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

P PROJECTION



ORDER INFORMATION

TFC-WPBP08R-08-LF

SERIES | REEL | LEADFREE | 08WAY

90°SMT | POST 8.0mm | BOTTOM CONTACT | PUSH PUSH

DESCRIPTION: Micro SD Socket Push-Push Type