

Specifications


Current Rating: 1Amp
 Insulation Resistance: 500MΩ Min.
 Dielectric Withstanding: 600VAC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C
 Max Process Temp: 230°C for 30~60 sec.
 (260°C for 10 seconds)

Materials

Contact Material: Phosphor Bronze
 Insulator Material: LCP, UL 94V-0
 All materials must be GP materials

Recommended P.C.Board

Hole Layout



Ordering Information

HMGDR1 - XX XX XXX L X

No. of Pins Per Row 02-40	Standard Plating 01=Gold Flash 02=Gold 3U" 11=Tin XX=Select Plating	Pin Length 001=2.0/1.6/2.5 XXX>Select A/R/B	Material L=LCP T=6T	Packing T=Tube TP=Tape+Reel
---------------------------------	---	---	---------------------------	-----------------------------------

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN	DATE	 www.allconnectors.eu info@allconnectors.eu Tel. +49 (0)711 / 358 110 20 Fax +49 (0)711 / 358 110 25	
		Andy2005.08.12			
X. ±	X°. ±5'	CHECK	DATE	FILE NAME (品名)	1.0mm Header R/A Type
.X ±0.38	.X' ±2'	APPRO.	DATE	PART NO (料号)	HMGDR1-XXXXXXXL
.XX ±0.25	.XX' ±1'			DRAWING NO.(图号)	HMGDR1-01
.XXX ±0.13	.XXX' ±0.5'	A4		SHEET: 1 of 1	