

Specifications


Current Rating: 1Amp
 Insulation Resistance: 500MΩ Min.
 Dielectric Withstanding: 200VAC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C

Materials

Contact Material: Brass
 Insulator Material: Polyester, UL 94V-0
 Nylon 6T
 All materials must meet Greenconn requirement for environment protection

Recommended P.C.B.Layout

(Tolerance: ±0.05)



Ordering Information

HMGSS1	-	XX	XX	XXX	L	X
No. of Pins Per Row	Standard Plating	Pin Length	Material	Packing		
02-40	01=Gold Flash 02=Gold 3U" 11=Tin XX=Select Plating	001=2.0/2.5 XXX=Select A/B	L=LCP T=6T	T=Tube TP=Tape+Reel		

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN DATE	 www.allconnectors.eu info@allconnectors.eu Tel. +49 (0)711 / 358 110 20 Fax +49 (0)711 / 358 110 25	
X. ± .38 .X ± 0.25 .XX ± 0.13	X' ± 5° .X' ± 2° .XX' ± 1° .XXX' ± 0.5°	Andy2005.08.12		
UNIT:mm	SCALE 1:1	CHECK DATE	FILE NAME (品名)	1.0mm Header DIP Type
A4	SHEET: 1 of 1	APPRO. DATE	PART NO (料号)	HMGSS1-XXXXXXL
			DRAWING NO.(图号)	HMGSS1-01
				REV.A0