



### Specifications

Current Rating: 1Amp  
 Insulation Resistance: 1000MΩ Min.  
 Dielectric Withstanding: 300V AC  
 Contact Resistance: 20mΩ Max.  
 Operating Temperature: -40°C to +105°C

### Materials

Contact Material: Brass  
 Insulation Material: Polyester, UL 94V-0  
 Nylon 6T  
 All materials must be GP materials

### Ordering Information

HMIDSH - XX XX XXX L B

No. of Pins Per Row: 02-40  
 Standard Plating: 01=Gold Flash, 02=Gold 3U", 11=Tin, XX=Select Plating  
 Pin Length: 001=4, 0/2, 0/2, 8, XXX=Select A/H/B  
 Material: L=LCP, T=6T  
 Material: B=Brass, P=Phosphoric Bronze, R=Round pin

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN DATE	 www.allconnectors.eu   info@allconnectors.eu Tel. +49 (0)711 / 358 110 20   Fax +49 (0)711 / 358 110 25	
.X ± 0.38 .XX ± 0.25 .XXX ± 0.13	X' ± 5° .X' ± 2° .XX' ± 1° .XXX' ± 0.5°	Andy2005.08.12		
UNIT:mm	SCALE 1:1	CHECK DATE	FILE NAME (品名)	1.27 Header DIP TYPE
A4	SHEET: 1 of 1	APPRO. DATE	PART NO (料号)	HMIDSH-XXXXXXLB
			DRAWING NO.(图号)	HMIDSH-01
				REV.AO