

Specifications

Current Rating: 1Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding: 300V AC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C


Materials

Contact Material: Brass
 Insulation Material: Polyester, UL 94V-0 LCP

All materials must meet Greenconn requirement for environment protection

Recommended P.C.Board Layout

(Tolerance: ±0.05)



Ordering Information

HMISSH - XX XX XXX L B

No. of Pins Per Row: 02-40
 Standard Plating: 01=Gold Flash, 02=Gold 3U", 11=Tin, XX=Select Plating
 Pin Length: 001=4, 0/2, 0/2, 8, XXX=Select A/H/B
 Material: L=LCP, T=6T
 Material: B=Brass, P=Phosphoric Bronze, R=Round pin

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN	DATE	 www.allconnectors.eu info@allconnectors.eu Tel. +49 (0)711 / 358 110 20 Fax +49 (0)711 / 358 110 25	
X. ± 0.38 .X ± 0.25 .XX ± 0.13	X° ± 5° .X° ± 2° .XX° ± 1° .XXX° ± 0.5°	Andy2005.08.12			
UNIT:mm	SCALE 1:1	APPRO.	DATE	PART NO (料号)	HMISSH-XXXXXXLB
A4	SHEET: 1 of 1			DRAWING NO.(图号)	HKISSH-01
					REV.AO