


Specifications

Current Rating: 1Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding: 300V AC/DC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C

Materials

Contact Material: Brass
 Insulation Material: Polyester, UL 94V-0 LCP
 All materials must meet Greenconn requirement for environment protection

Recommended P.C.Board Hole Layout
 Hole Layout
 (Tolerance: ±0.05)



Ordering Information

HMJSS X - XX XX XXX L B

Material High 1=1.0MM 2=2.0MM 3=3.0MM 4=2.54MM 5=1.5MM 6=1.7MM 7=1.7MM 8=2.5MM


No. of Pins Per Row 02-40

Standard Plating 01=Gold Flash 02=Gold 3U" 11=Tin XX=Select Plating

Pin Length 001=A=4.0 /B=2.8 XXX=Select A/B

Material L=LCP T=6T

Material B=Brass P=Phosphoric Bronze R=Round pin

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN	DATE	 www.allconnectors.eu info@allconnectors.eu Tel. +49 (0)711 / 358 110 20 Fax +49 (0)711 / 358 110 25	
		Andy2005.08.12	CHECK		
X. ± .38	X°. ±5°	APPRO.	DATE	FILE NAME (品名)	1.27 DIP TYPE CONNECTOR
.XX ±0.25	.X° ±2°			PART NO (料号)	HMJSSX-XXXXXXXXLB
.XXX ±0.13	.XXX° ±1°			DRAWING NO.(图号)	HMJSSX-01
UNIT:mm	SCALE 1:1				REV.A0
A4	SHEET: 1 of 1				