

Recommended P.C.B Layout

MATERIAL

Insulator : 30% Glass fiber PBT

Contact Pin : Brass

SPECIFICATION

Current Rate : 1 AMP

Insulation Resistance : 5000MΩMin. at DC 500V

Contact Resistance : 20mΩMax. at DC 100mA

Dielectric Voltage : AC 500V for one minute

Operation Temperature : -40°C to + 105°C

| POLES | DIM E | POLES | DIM E |
|-------|-------|-------|-------|
| | | 23 | 44.00 |
| 2 | 2.00 | 24 | 46.00 |
| 3 | 4.00 | 25 | 48.00 |
| 4 | 6.00 | 26 | 50.00 |
| 5 | 8.00 | 27 | 52.00 |
| 6 | 10.00 | 28 | 54.00 |
| 7 | 12.00 | 29 | 56.00 |
| 8 | 14.00 | 30 | 58.00 |
| 9 | 16.00 | 31 | 60.00 |
| 10 | 18.00 | 32 | 62.00 |
| 11 | 20.00 | 33 | 64.00 |
| 12 | 22.00 | 34 | 66.00 |
| 13 | 24.00 | 35 | 68.00 |
| 14 | 26.00 | 36 | 70.00 |
| 15 | 28.00 | 37 | 72.00 |
| 16 | 30.00 | 38 | 74.00 |
| 17 | 32.00 | 39 | 76.00 |
| 18 | 34.00 | 40 | 78.00 |
| 19 | 36.00 | 41 | 80.00 |
| 20 | 38.00 | 42 | 82.00 |
| 21 | 40.00 | 43 | 84.00 |
| 22 | 42.00 | 44 | 86.00 |

All Connectors


www.allconnectors.de info@allconnectors.de
Tel.: 0049 711 7009503 Fax: 0049 711 7009504
70794 Filderstadt - Germany Kettenerstr. 25

RoHS Compliant


DRAWING BY CY
CHECKED BY GENIUS
UNIT / mm SCALE 1 : 1
DATE
SIZE A4 PROJECTION

TOLERANCES ARE

X ±
.X ± 0.30
.XX ± 0.20
.XXX ±
ANG ± 3°



ORDER INFORMATION



DESCRIPTION: PIN HEADER 2.00*2.00mm
RIGHT ANGLE TYPE, DUAL ROWS