

Recommended P.C.B Layout

MATFRIAL

Insulator : NYLON 6T or 9T

Contact Pin : Brass

SPECIFICATION

Current Rate : 3 AMP

Insulation Resistance : 5000MΩMin. at DC 500V

Contact Resistance : 20mΩMax. at DC 100mA

Dielectric Voltage : AC 500V for one minute

Operation Temperature : -40°C to + 105°C

POLES	DIM E	POLES	DIM E
2	2.54	26	63.50
3	5.08	27	66.04
4	7.62	28	68.58
5	10.16	29	71.12
6	12.70	30	73.66
7	15.24	31	76.20
8	17.78	32	78.74
9	20.32	33	81.28
10	22.86	34	83.82
11	25.40	35	86.36
12	27.94	36	88.90
13	30.48	37	91.44
14	33.02	38	93.98
15	35.56	39	96.52
16	38.10	40	99.06
17	40.64	41	101.60
18	43.18	42	104.14
19	45.72	43	106.68
20	48.26	44	109.22
21	50.80	45	111.76
22	53.34	46	114.30
23	55.88	47	116.84
24	58.42	48	119.38
25	60.96	49	121.92
		50	124.46

All Connectors

www.allconnectors.de info@allconnectors.de
Tel.: 0049 711 7009503 Fax: 0049 711 7009504
70794 Filderstadt - Germany Kettenerstr. 25

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT/ mm SCALE 1:1


DATE

SIZE A4

TOLERANCES ARE

X ±
X ± 0.30
.XX ± 0.20
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

H-DNxT-2Xxx-LF



DESCRIPTION: PIN HEADER 2.54*2.54mm STRAIGHT TYPE, DUAL ROWS