

Specifications


Current Rating: 3Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding: 600V AC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C

Materials

Contact Material: Brass
 Insulation Material: Polyester, UL 94V-0 PBT
 All materials must be GP materials


Recommended P.C.Board

Hole Layout
 (Tolerance: ±0.05)



Ordering Information

HMNDS	X	-	XX	XX	XXX	P	B
	└─┘		└─┘	└─┘	└─┘	└─┘	└─┘
Material High	No. of Pins	Standard Plating	Pin Length	Material	Material		
1=1.5MM	Per Row	01=Gold Flash	001=6.0 /3.0	L=LCP	B=Brass		
2=2.54MM	02=40	02=Gold 3U"	XXX>Select A/B	T=NLGT	P=Phosphoric Bronze		
3=4.3MM		11=Tin		P=PBT			
4=7.4MM		XX>Select Plating					

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN	DATE	 www.allconnectors.eu info@allconnectors.eu Tel. +49 (0)711 / 358 110 20 Fax +49 (0)711 / 358 110 25	
		Andy2005.08.12			
X. ±0.38	X' ±5°	CHECK	DATE	FILE NAME (品名)	2.54MM Header Dip TYPE
.XX ±0.25	.X' ±2°			PART NO (料号)	HMNDSX-XXXXXXXXPB
.XXX ±0.13	.XX' ±1°	APPRO.	DATE	DRAWING NO.(图号)	HMNDSX-01
	.XXX' ±0.5°				REV.A0
UNIT:mm	SCALE 1:1				
A4	SHEET: 1 of 1				