

Recommended P.C.B Layout


MATERIAL

Insulator : 30% Glass fiber PBT
 Contact Pin : Brass, Gold Flash

SPECIFICATION

Current Rate : 3 AMP
 Insulation Resistance : 5000MΩMin. at DC 500V
 Contact Resistance : 20mΩMax. at DC 100mA
 Dielectric Voltage : AC 500V for one minute
 Operation Temperature : -40°C to + 105°C

<p>www.allconnectors.de Tel.: 0049 711 7009503 70794 Filderstadt - Germany</p> <p>info@allconnectors.de Fax: 0049 711 7009504 Kettenerstr. 25</p>	RoHS Compliant		TOLERANCES ARE	
	DRAWING BY CY		X ±	∓ 0.30
	CHECKED BY GENIUS		.XX ±	
	UNIT / mm	SCALE 1 : 1	.XXX ±	∓
	DATE		ANG ±	
SIZE A4	PROJECTION			



ORDER INFORMATION

HSB-Dxxxxyzz-2Xxx-LF

SERIES	DIP180°	TOTAL	CONTACT	DIP	LEADFREE
		168:16.8mm	72:7.2mm	30:3.0mm	
				2X02:04WAY	
				2X50:100WAY	

DESCRIPTION: PIN HEADER 2.54*2.54mm STRAIGHT STACK