


■ MATERIAL


Insulator : High Temperature Polyester
Contact Pin : Brass

■ SPECIFICATION

Current Rate : 7 AMP
Insulation Resistance : 1000MΩMin.
Withstanding Voltage : 1500V AC
Contact Resistance : 20mΩMax.
Operation Temperature : -40°C to + 105°C



■ Detail Dimensions



■ Recommended P.C.B Layout



■ Order Information

27 x - 91 - xx G B xx
1 2 3 4

- 9: Straight Type
A: Straight Stack Type
- No. of contacts per row
- G: Gold Flash
T: Tin Plating
- Pinrex internal code

If you need other dimensions,
please fill out DIM A/B/C and
contact our sales representatives.

DIM A	DIM B	DIM C

■ Number Of Contacts

Unit: mm

Poles	DIM E	Poles	DIM E	Poles	DIM E	Poles	DIM E	Poles	DIM E	Poles	DIM E	Poles	DIM E	Poles	DIM E
		8	27.72	15	55.44	22	83.16								
2	3.96	9	31.68	16	59.40	23	87.12								
3	7.92	10	35.64	17	63.36	24	91.08								
4	11.88	11	39.60	18	67.32										
5	15.84	12	43.56	19	71.28										
6	19.80	13	47.52	20	75.24										
7	23.76	14	51.48	21	79.20										