

Specifications

Current Rating: 7.9Amp
 Insulation Resistance: 5000M Ω Min.
 Dielectric Withstanding: 1500V AC/DC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -55°C to +125°C


MATERIAL:

-HOUSING: LCP. FLAMMABILITY UL94-V0
 OR OTHER HIGH LEVEL PLASTIC, COLOR:BLACK.
 -Contact: Brass Δ

All materials must be GP materials

Recommended P.C.B. Layout


(Tolerance:0.05mm)



Ordering Information

HMRSS1 - XX XX XXX L B

No. of Pins Per Row 02-20	Standard Plating 01=Gold Flash 02=Gold 3U" 11=Tin XX=Select Plating	Pin Length 001=8.0 /3.5/3.5	Material L=LCP T=NL6T	Material B=Brass P=Phosphoric Bronze
---------------------------------	---	--------------------------------	-----------------------------	--

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN	DATE	 www.allconnectors.eu info@allconnectors.eu Tel. +49 (0)711 / 358 110 20 Fax +49 (0)711 / 358 110 25	
		Andy2005.08.12	CHECK		
X. ±	X'. ±5'	APPRO.	DATE	FILE NAME (品名)	5.08MM Header R/A TYPE
.X ±0.38	.X' ±2'			PART NO (料号)	HMRSR1-XXXXXXXLB
.XX ±0.25	.XX' ±1'			DRAWING NO.(图号)	HMRSR1-01
.XXX ±0.13	.XXX' ±0.5'				REV.A0
UNIT:mm	SCALE 1:1				
A4	SHEET: 1 of 1				