




RoHS compliant

SPECIFICATION


Current Rating: 1 Amp
 Insulation Resistance: 5000 Megohms min
 Contact Resistance: 20 m ohms Max
 Dielectric Withstanding: AC 500 V
 Operating Temperature: -65 ° C to +125° C
 Contact Material: Brass
 Insulator Material: Polyester, UL 94V-0
 Standard : PBT



Ordering Code:

EPD01- X - X - A - X - X - X
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No:
- ② No. of Contact: 01 TO 40
- ③ Contact Plating:
 A: Gold Flash
 E: 3u" Gold
 B: 10u" Gold
 C: 15u" Gold
- ④ Connector Type:
 A: Single Row
- ⑤ Pin Length:
 A:11.6 B:6.0 C:3.0 (Standard)
 Please mark the desired length in the A/B/C
- ⑥ Code Packing:
 0: Bag

UNLESS OTHERWISE SPECIFIED TOLERANCE ANG. 0. 0 ±0.25 00 ±0.2	 <small>www.allconnectors.eu info@allconnectors.eu Tel. +49 (0)711 / 358 110 20 Fax +49 (0)711 / 358 110 25</small>
DRAWN	TITLE: 2.54 mm Pin Header, Straight Type Single Row
CHECKED	
APPROVED	DRAWN NO: EPD01-XXAX-1
REV	DESCRIPTION
DATE	PRODUCT NO. EPD01-XXAXX