



- NOTES
1. MATERIAL & FLASH/PLATED
 - 1.1 HOUSING: HIGH TEMP. THERMOPLASTIC+GLASS FIBRE [UL 94V-0]; COLOR: BLACK
 - 1.2 PROBE: BRASS
 - .PLATING: TOP PROBE 10u" MIN. GOLD ON ALL, BOTTOM PROBE 3u" MIN. GOLD ON ALL, BUSHONG PROBE 3u" MIN. GOLD ON ALL,
 - 1.3 SPRING: STAINLESS
 2. PRODUCT SPECIFICATION
 - 2.1 DISPLACEMENT: 1.0mm
 - 2.2 CONTACT RESISTANCE: 50MILLIOHMS MAX.
 - 2.3 NORMAL FORCE: PRE-LOAD=0gf MIN. DISPLACEMENT: 1.0mm FORCE=110±30gf
 - 2.4 DURABILITY: 10,000CYCLE [SPRING FORCE 20% LOSS]. NOTES: REDUCTION OF ORIGINAL FORCE 20% LOSS.
 3. PC BOARD THICKNESS: 1.0mm REF.

						UNLESS OTHERWISE SPECIFIED TOLERANCE		 <small>www.allconnectors.eu info@allconnectors.eu Tel. +49 (0)711 / 358 110 20 Fax +49 (0)711 / 358 110 25</small>			
						ANG. ±5 0. ±0.3 .0 ±0.25 .00 ±0.20					
						SCALE: AS SHOWN	UNIT: mm				
						DRAWN Willis		2009/03/04		DRAWN NAME: POGO Pin Single pin H=4mm	
						CHECKED / /		APPROVED / /		PRODUCT NO. 303A-261420-000	
REV.						DESCRIPTION		DATE		 SIZE A4 REV. FILE NAME: 303A-261420-000_B_1	