



NO.	NAME	MATERIAL	FINISH	Q'TY
1	BARREL	C.R.S T:0.30	TIN PLATED	1
2	RING	PBT G.F.	BLACK	1
3	INSULATOR	PBT G.F.	WHITE	1
4	BRACKET	C.R.S T:0.70	TIN PLATED	1
5	TERMINAL	BRASS T:0.25	TIN PLATED	1

RCA-JR08BK-02-LF
LEADFREE
RoHS Compliant

Specification:

Contact Resistance: 30m Ohm. Max. At AC 100mA Max.1KHz.
Insulation Resistance: 100M Ohm Min. At 500V DC.
Rated Voltage And Current: DC 12V,2A Max ; AC 100V,1A Max.
Dielectric Withstanding Voltage: 500VAC At 60Hz For 1 Minute.
Durability (Life Test): 4000 Cycles.
Insertion Force: 0.3~3.0 Kg.
Extraction Force: 0.3~3.0Kg.

Allconnectors

www.allconnectors.de
Tel.: 0049 711 7009503
70794 | Heerstadt - Germany

info@allconnectors.de
Fax: 0049 711 7009504
Kettnerstr. 2b

PART NO. RCA-JR08BK-02

DWG NO. RCA-JR08BK-02

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

X ± 0.2
.XX ±
.XXX ±
ANG

DESCRIPTION: RCA JACK

AREA

REVISIONS

HK

DATE