



NOTES

***Material:**

- 1.Body: PPS UL 94V-0 Rated, Color:Black;
- 2.Cover: LCP UL 94V-0 Rated, Color:Black;
- 3.Contact: Phosphor Bronze;
- 4.Contact Plating: Gold Plating Over Nickel on Contact Area, Tin Plating on Solder Tail.

***Specification:**

- 1.Current Rating: 0.5 AMP. Max.;
- 2.Dielectric Withstanding Voltage: 500V AC R.M.S For One Minute;
- 3.Insulation Resistance: 1000 M Ohms Min. AT 500V AC;
- 4.Contact Resistance: 30 M Ohms Max.;
- 5.Operating Temperature: -25°C to +85°C;
- 6.Processing Temp: 245°C for 30~60 Seconds Max.;
- 7.Durability: 5000 Cycles.

<p>www.allconnectors.de Tel.: 0049 711 7009503 70794 Filderstadt - Germany</p> <p>info@allconnectors.de Fax: 0049 711 7009504 Kettenerstr. 25</p>	RoHS Compliant		TOLERANCES ARE		
	DRAWING BY CY		X ±	.XX ± 0.10	
	CHECKED BY GENIUS		.X ± 0.20		
	UNIT/ mm	SCALE 1 : 1	.XXX ±	ANG ±	
	DATE				
SIZE A4	PROJECTION				

ORDER INFORMATION			
SCV-W2523X-06-LF			
SERIES	90°SMT	06WAY	LEADFREE
PAD TO PAD 25.2mm		NON POST	
		BODY HIGH 2.3mm	
DESCRIPTION: Sim Card 6Pin Without Post			