



- NOTES:
- Material :  
Housing : Thermoplastic UL94V-0  
Contact : BERYLLIUM C17200R-H,T=0.10mm.
  - Plating :  
Contact Plating - Gold over 45u" MIN.Nickel  
Solder Tail Plating - Gold Flash over 45u" MIN.Nickel
  - Contact Forces :  
Max. 0.5 N For 0.5mm Contact Deflection.  
Min. 0.25 N For 0.5mm Contact Deflection.
  - Specification :  
Withstanding Voltage:500V AC initial and 250 V AC final at sea level for 1 Minute  
Insulation Resistance:1000M Ohms  
Voltage Rating:5 Volts Max  
Current Rating:10mA Max  
Contact Resistance:30m Ohms Max  
Operating Temperature:-40°C~+85°C  
Insertion Cycles:20,000 Times
  - Application:  
For SIM Card Use Only

SCX-W1505X-06-LF  
LEADFREE  
RoHS Compliant

**Allconnectors**  
www.allconnectors.de  
Tel: 0049 711 309308  
70751 Ploherstadt - Germany

info@allconnectors.de  
Fax: 0049 711 309309  
Kettnerstr. 25

PART NO. SCX-W1505X-06

DWG NO. SCX-W1505X-06

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2  
.XX ± 0.1  
.XXX ±  
AWG

DESCRIP TION:			
AREA	REVISIONS	HK	DATE