



**Material:**

- Item ① Insulator(lever): Thermoplastic (UL94V-0)
- Item ② Insulator(housing): Thermoplastic (UL94V-0)
- Item ③ Wire guard: Stainless steel
- Item ④ Terminal Body(contact pin): PhBz.

**Electrical:** cULus

- Voltage rating: 125V
- Current rating: 4A
- Wire range:
- Solid wire(AWG): 20-28
- Stranded wire(AWG): 20-28
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -33°C to +105°C

TBX025-SVB-xx-LF  
LEADFREE

RoHS Compliant

POLE		2	3	4	5	6	7	8	9	10	11	12	
A		5.60	8.10	10.60	13.10	15.60	18.10	20.60	23.10	25.60	28.10	30.60	
B		2.50	5.00	7.50	10.00	12.50	15.00	17.50	20.00	22.50	25.00	27.50	
Tol.		±0.10						±0.15					
POLE	13	14	15	16	17	18	19	20	21	22	23	24	
A	33.10	35.60	38.10	40.60	43.10	45.60	48.10	50.60	53.10	55.60	58.10	60.60	
B	30.00	32.50	35.00	37.50	40.00	42.50	45.00	47.50	50.00	52.50	55.00	57.50	
Tol.	±0.20						±0.30						

PART NO. TBX025-SVB-xx

DWG NO. TBX025-SVB-xx

CHECKED BY CY

TOLERANCES ARE

DESCRIP TION:

FILE NO.

DRAWING BY

.X ± 0.2  
.XX ±  
.XXX ±  
AWG

AREA

REVISIONS

HK

DATE

UNIT / mm

SCALE 1:1

PROJECTION



**All Connectors**

www.allconnectors.eu | info@allconnectors.eu  
Tel. +49 (0)711 / 358 110 20 | Fax +49 (0)711 / 358 110 25