



P.C.B. LAYOUT(REF)

- NOTES:**
1. Rating: 300V 4A (IEC 130V)
PITCH: 2.54mm
 2. Insulation Withstands Voltage:
AC 1000 V/MIN
 3. Insulation Resistance:
500M Ω or more at DC500V
 4. Using Temperature Range:
-40°C ~ +105°C
 5. Suitable Electric Wire:
AWG 28~20 (IEC 0.5mm²)
 6. Undimensioned Tolerances:

—	∧	∕	0.05/10
⊥	∕∕	≡	0.2/10
PITCH ERROR			0.05/10
UNDIMENSIONED TOLERANCES			±0.3

TBX026-A15GE-xx-LF
LEADFREE
RoHS Compliant

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
5	END COVER	D119L9XX00	1	PA66(VI)	MO01 GREY
4	LEVER	D119L8XX00	P	POM	MO05 WHITE
3	CLAMP	X000003200	P	Stainless Steel	
2	SOLDER PIN	D119B00400	P	COPPER	Tin Plated
1	HOUSING	D119P7XX00	P	PA66(VI)	MO01 GREY

Allconnectors
www.allconnectors.de
Tel.: 0049 711 700503
70/04 Hilderstadt - Germany

Info@allconnectors.de
Fax: 0049 711 700504
Kettnerstr. 2b

PART NO. TBX026-A15GE-xx		CHECKED BY CY		TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIPTION:			
DWG NO. TBX026-A15GE-xx		DRAWING BY						
UNIT / mm	SCALE 1:1	PROJECTION			AREA	REVISIONS	HK	DATE