

P.C.B. LAYOUT

Dimension

|       |                     |
|-------|---------------------|
| DIM A | $(N+1) \times 2.54$ |
| DIM B | $(N-1) \times 2.54$ |


N=Number of poles  $\Delta$

| POLES   | DIM A      | DIM B      |
|---------|------------|------------|
| 2p-8p   | $\pm 0.15$ | $\pm 0.15$ |
| 9p-12p  | $\pm 0.25$ | $\pm 0.25$ |
| 13p-18p | $\pm 0.30$ | $\pm 0.30$ |
| 19p-24p | $\pm 0.40$ | $\pm 0.40$ |

Material

- Terminal body (Contact pin): Brass
- Wire guard: Stainless steel
- Surface of solder tail: Tin plated
- Insulator (housing): Thermoplastic (UL94V-0)

Electrical cULus

- Voltage rating: 150VAC
- Current rating: 2A
- Wire range:
- Solid wire(AWG): 20-26
- Stranded wire(AWG): 20-26
- Pull force:
- Screw:
- Wire strip length: 9-10mm
- Withstanding Voltage: 1.3KV
- Operating temperature:  $-40^{\circ}\text{C}$  to  $+115^{\circ}\text{C}$
- Soldering temperature:  $250^{\circ}\text{C} \pm 10^{\circ}\text{C} / 5 \text{ Sec}$   $\Delta$
- Safety Approval: 

TBX026-D13-xx-LF  
02-24WAY LEADFREE

RoHS Compliant

**Allconnectors**

www.allconnectors.de  
Tel.: 0049 711 7009503  
70794 Filderstadt - Germany

info@allconnectors.de  
Fax: 0049 711 7009501  
Kettnerstr. 25

PART NO. TBX026-D13-xx

DWG NO. TBX026-D13-xx

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION 

TOLERANCES ARE

- X.  $\pm 0.5$
- .X  $\pm 0.3$
- .XX  $\pm 0.1$
- .XXX  $\pm$
- ANG

DESCRIPTION:

AREA

REVISIONS

DATE