



- Material:**
- Item (A) Lever: Thermoplastic (UL 94V-0)
 - Item (B) Terminal housing: Thermoplastic (UL 94V-0)
 - Item (C) Wire guard: Stainless steel
 - Item (D) Solder Pin: Brass.Tin plated

- Electrical:** cULus
- Voltage rating: 300 V
 - Current rating: 10 A
 - Wire range:
 - Solid wire(AWG): 16-24
 - Stranded wire(AWG): 16-24
 - Wire strip length: 12-13 mm
 - Withstanding Voltage: 1.6KV
 - Operating temperature: -40°C to +115°C
 - Soldering temperature: 250°C±10°C/5 Sec
 - Safety Approval:

TBX035-R08-xx-LF
 02:02WAY LEADFREE
 24:24WAY
 RoHS Compliant

N=NUMBER OF CONTACTS

DIM	TOL				
	2P--6P	7P--12P	13P--18P	19P--24P	
Dim L	N×3.5±0.70	±0.15	±0.20	±0.30	±0.40
Dim P	(N-1)×3.5	±0.15	±0.20	±0.30	±0.40

All Connectors

www.allconnectors.de
 Tel.: 0049 711 7005503
 70734 Filderstadt - Germany

info@allconnectors.de
 Fax: 0049 711 7005504
 Kellerstr. 25

PART NO. TBX035-R08-xx

DWG NO. TBX035-R08-xx

FILE NO.

UNIT / mm SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

X ± 0.2
 .XX ±
 .XXX ±
 ANG

DESCRIPTION:				
AREA	REVISIONS	HK	DATE	