



Material:

- Item ① Insulator(lever): Thermoplastic (UL94V-0)
- Item ② Insulator(housing): Thermoplastic (UL94V-0)
- Item ③ Wire guard: Stainless steel
- Item ④ Terminal Body(contact pin): PhBz.

Electrical: cULus

- Voltage rating: 300 V
- Current rating: 8 A
- Wire range:
- Solid wire(AWG): 16-28
- Stranded wire(AWG): 16-28
- Wire strip length: 6-7 mm
- Withstanding Voltage: 1.3 KV
- Operating temperature: -33°C to +105°C

TBX035-SVCC-xx-LF
LEADFREE

RoHS Compliant

POLE		2	3	4	5	6	7	8	9	10	11	12	
A		///	///	///	///	///	25.30	28.80	32.30	35.80	39.30	42.80	
B		///	///	///	///	///	21.00	24.50	28.00	31.50	35.00	38.50	
Tol.								±0.15					
POLE	13	14	15	16	17	18	19	20	21	22	23	24	
A	46.30	49.80	53.30	56.80	60.30	63.80	67.30	70.80	74.30	77.80	81.30	84.80	
B	42.00	45.50	49.00	52.50	56.00	59.50	63.00	66.50	70.00	73.50	77.00	80.50	
Tol.	±0.20						±0.30						

Allconnectors

www.allconnectors.de
+49 3649 711 2009-013
70794 Filberstadt Germany

info@allconnectors.de
Fax: +49 3649 711 2009-014
Kilbinger Str. 25

PART NO. TBX035-SVCC-xx

DWG NO. TBX035-SVCC-xx

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE