



MATERIALS:

1. HOUSING: THERMOPLASTIC, UL 94V-0 RATED.
2. COVER: THERMOPLASTIC, UL 94V-0 RATED.
3. CONTACTS: COPPER ALLOY, SELECTIVE GOLD PLATED
4. SHELL: SPCC, NICKEL PLATED.
5. HARPOON: COPPER ALLOY, TIN OVER NICKEL

SPECIFICATION:

1. RATED CURRENT: 0.30A/CONTACT
2. INSULATION RESISTANCE: 500MOHM MIN.
3. DIELECTRIC WITHSTANDING VOLTAGE: 250V AC FOR 1 MINUTE.
4. OPERATING TEMPERATURE: -25°C TO +85°C

VHCB1-SRN-068-LF
LEADFREE

RoHS Compliant

Allconnectors

www.allconnectors.de
Tel.: 0049 711 709503
70794 Filderstadt - Germany

info@allconnectors.de
Fax: 0049 711 709504
kettnerstr. 25

PART NO. VHCB1-SRN-068

DWG NO. VHCB1-SRN-068

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

X ± 0.2
.XX ± 0.1
.XXX ±
AWG

DESCRIPTION:

68 POSITION CHAMP STACKED
PITCH 0.80, RIGHT ANGLE TYPE

AREA

REVISIONS

HK

DATE